

CANTER



Canter 515 Wide Cab Alloy Tray

4X2 / WIDE CAB / DUONIC OR MANUAL



**OUR SAFEST CANTER EVER WITH AEBS, LDWS AND ESP STANDARD
ALLOY TRAY WITH TWO-PIECE DROP SIDES
30,000KM SERVICE INTERVALS**

GVM

4,495_{KG}

GCM

7,995_{KG}

Power/Torque

110_{KW} / 370_{NM}

- Can be driven on a passenger car licence

SPECIFICATIONS

MODEL

- A 4x2 515 Built Ready Wide Cab Alloy Tray 6 Sp. Duonic AMT (FEB21ER3SFBN-B10)
- B 4x2 515 Built Ready Wide Cab Alloy Tray MWB 5 Sp. Manual (FEB21ER4SFBC-B10)

WHEEL BASE

- 3400mm
- 3400mm

GVM (optional)


- 4,495kg
- 4,495kg

GCM (optional)

- 7,995kg
- 7,995kg

Engine

| | |
|-----------------------------|---|
| Engine Version | FUSO 4P10-T4 Diesel |
| Configuration | 4 Cyl. In-line DOHC, 4-Valve |
| Type | Variable Geometry Turbo Charged Air to Air Intercooled |
| Displacement | 3 litre (2998cc) |
| Bore | 95.8mm |
| Stroke | 104mm |
| Power (DIN) | 110kW @ 2840~3500 rpm |
| Torque (DIN) | 370Nm @ 1350~2840 rpm |
| Maximum Engine Speed | 4100 rpm |
| Compression Ratio | 17.5:1 |
| Cooling System / Oil Cooler | Water cooled, 13.7L capacity/ Plate type engine oil cooler |
| Air Cleaner | Paper Element Type with Restrictor Indicator. Vertical Intake Mounted on Clean Air Side (RH) |
| Emission Control | Diesel Particulate Filter (DPF) Exhaust Dash Display DPF Status 0~9 (Empty~Full) Parked Regeneration possible from 7~9 |
| Emission Level | ADR 80/03 & EEV rated (Enhanced Environmentally-Friendly Vehicle) Euro 5 |



Fuel

| | |
|------------------|--|
| Injection System | Bosch Common Rail Direct Injection Bosch Piezo Technology Injectors |
| Tank Type | Rectangular Steel Tank with Locking Cap |
| Fuel Capacity * | 100 Litres |
| Filtration | Filter with Water Separator and Indicator Sensor |
| Notes | *Max Fill to approx 95% of Air Capacity |

Cooling

| | |
|-----------|---|
| Fan Drive | Thermo modulated continuous control (Viscous) |
| Radiator | Corrugated Fin with Expansion Tank |

Electrical

| | |
|-----------------------|----------------------------------|
| Voltage | 12V Negative Earth |
| Alternator Capacity | A 12V-140 amp B 12V-110 amp |
| Starter Capacity | 12V-2.0kW |
| Battery Capacity | 2x12V, 70Ah/5hr |
| Battery Specification | 115D31LX2 |
| Headlamp Type | Halogen |
| Headlamp Capacity | 2x55W/60W |

Clutch

| | | |
|--------------|---|---|
| Clutch Model | A Duonic Automated Manual (no clutch pedal) | B FUSO C4W30 |
| Type | A Dual Clutch (Wet Multi-plate) | B Single Dry Plate, Direct Hydraulic Type |

Transmission

| | | |
|-------------|--|--|
| Version | A FUSO Duonic M038S6 | B FUSO M038S5 |
| Type/Speeds | A 6 Speed Automated Manual with Auto and Manual Modes | B 5 Speed with In-Dash Gearshift Lever |
| Features | A Virtually Instant Gear Changes In-Dash Gear Lever with Park Brake Position ECO Mode to Minimise Fuel Usage | B Synchromesh 2nd-5th |
| Ratios | A 1st: 5.397 2nd: 3.788 3rd: 2.310 4th: 1.474 5th: 1.000 6th: 0.701 Rev. 5.397 | B 1st: 5.494 2nd: 3.193 3rd: 1.689 4th: 1.000 5th: 0.723 Rev. 4.494 |
| PTO Opening | LH Side | |

Front Axle

| | |
|--------------|--|
| Axle Version | FUSO F200T |
| Type | Independent Front Suspension |
| Capacity * | 2300kg |
| Notes | *See MAX LOADING for vehicle capacity. |

Front Suspension

| | |
|------|--|
| Type | Double Wishbone Independent Front Suspension with Coil Springs and Shock Absorbers |
|------|--|

Rear Axle

| | |
|--------------|--|
| Type | Full Floating Banjo Type |
| Axle Version | FUSO R030T |
| Capacity* | 3800kg |
| Ratio | 4.444:1 |
| Notes | *See MAX LOADING for vehicle capacity. |

Rear Suspension

| | |
|------------------|-------------------------------------|
| Type | Steel Suspension |
| Details | Parabolic Leaf with Shock Absorbers |
| Size Main Leaves | 1100x70mm |

Max Loading

| | |
|-------|--------|
| Front | 2180kg |
| Rear | 3800kg |
| Total | 4500kg |

Steering

| | |
|-----------------|----------------------------|
| Type | Rack & Pinion |
| Steering Column | Tilt/Telescopic Adjustable |
| Power Assist | Standard |

SPECIFICATIONS

MODEL

| | |
|----------|---|
| A | 4x2 515 Built Ready Wide Cab Alloy Tray 6 Sp. Duonic AMT (FEB21ER3SFBN-B10) |
| B | 4x2 515 Built Ready Wide Cab Alloy Tray MWB 5 Sp. Manual (FEB21ER4SFBC-B10) |

WHEEL BASE

| |
|--------|
| 3400mm |
| 3400mm |

GVM (optional)

| |
|---------|
| 4,495kg |
| 4,495kg |

GCM (optional)

| |
|---------|
| 7,995kg |
| 7,995kg |

Brakes

| | | |
|------------|---|--|
| Type | Hydraulic Dual Circuit with Front and Rear Discs Single Calliper Front and Rear | |
| Size Front | 276x28mm | |
| Size Rear | 276x28mm | |
| Features | A ABS plus EBD (Electronic Brake Distribution) Exhaust Brake Fuso Brake Priority System ESP (Electronic Stability Program) | B ABS plus EBD (Electronic Brake Distribution) Exhaust Brake Brake Priority System |
| Park Brake | Transmission Mounted | |

Wheels & Tyres

| | |
|--------------------|--|
| Wheel Type | 7 x Single Piece Disc Rims (Including Spare) |
| Wheel Size | 16.0x5.5K-115 |
| Wheel Stud Pattern | 5 Stud 208 PCD |
| Tyre Size All | 185/85R16 111/109 |
| Spare Tyre Carrier | Provided |

Chassis

| | |
|------------------|----------------------------|
| Type | Reinforced Tapered Channel |
| Size | 188x60x4mm |
| Width | 748mm |
| Tensile Strength | 540 MPa |

Instruments

| | |
|----------------------------|--|
| Gauges | Speedometer with Odometer Tachometer Fuel Level Water Temperature |
| Colour Information Display | Fuel Consumption DPF Bar Chart from 1~9 Water Temperature Maintenance Reminder System Tripmeters |

Multi-Media Package

| | |
|-----------------------------|---|
| Satellite Navigation | Maps with heavy vehicle weight, length, height & hazardous material selectable restrictions with 3 years of Map updates |
| Colour Display | 6.1 inch LCD with touch screen control |
| Phone Connectivity | Bluetooth® hands free |
| Audio Visual Entertainment | CD/DVD player and Digital radio DAB+ (also AM/FM for areas not covered by DAB+) |
| Reversing Camera Compatible | Display can accept up to 3 cameras# |
| Notes | # Cameras available through spare parts |

Standard Features

| | | |
|------------------------------------|--|----------------|
| Airbag(s) | Dual Air Bags and Seat Belt Pre-Tensioners (Driver & Far Side Passenger) | |
| Active Safety Features | ABS plus Electronic Brake force Distribution (EBD) Advanced Emergency Braking (AEBS) Anti-Slip Regulator (ASR) Electronic Stability Program (ESP) Lane Departure Warning System (LDWS) | |
| Electronic Stability Program (ESP) | A Yes | B No |
| Idle Stop Start (ISS) | A Yes | B No |
| Cruise Control | A Yes | B No |
| Hill Start System | Yes | |
| Cab Cooling & Heating | Air Conditioner / Heater / Demister | |
| Accessory Power | 12V Accessory Power Outlet / Cigar Lighter | |
| Driving | Fuso Multimedia Unit Keyless Central Locking Electric Windows Cup Holders (2) | |
| Storage | Dual Overhead Storage Pockets In-Dash Centre Document Storage Door Storage Pockets Dash Storage Tray (1 DIN) Coat Hooks | |
| Cab: External | Front End-Outline Marker Lamps Door Side Impact Beams | |
| Chassis | Reverse Warning Buzzer Factory Reverse Camera with Infrared Display and Audible Pickup (Supply only in Cabin) | |

Cab Features

| | | |
|--------------------------|--|-----------------|
| Type | All Steel Forward Control Manual Tilt | |
| Cab Structure | ECE-R29 European Cab Strength Approved | |
| Mounting | Hydroelastic 4 Point | |
| Additional Engine Access | A Removable Engine Access Panel | B N/A |
| Colour | Natural White | |
| Windscreen Wipers | 2 Speed + Intermittent Cycle with Integrated Washer Nozzles | |
| Rear Vision Mirrors | 1 x Internal 2 x External Convex (ECE 46) - Heated | |
| Seating Capacity | 3 | |
| Seat Belts | Lap Sash Belts for Outside Seating Positions Lap Belt for Centre Seat | |
| Seat (driver) | Suspended with Weight Adjustment, LH Arm Rest and Lumbar Support | |
| Seats (passenger) | Flat Folding, 2 Passenger Bench | |

Service Intervals

| | |
|-----------|---|
| Interval* | 30,000km or 12 Months (whichever occurs first) |
| Notes | * based on normal operating conditions and may be reduced when operating under severe conditions. |

Warranty

| | |
|--------------------------------|--|
| Basic/Powertrain | 5 Years or 200,000kms (whichever occurs first) |
| Cab Perforation/Anti Corrosion | 5 Years |
| Body | 1 Year/Unlimited kms |

SPECIFICATIONS

MODEL

- A 4x2 515 Built Ready Wide Cab Alloy Tray 6 Sp. Duonic AMT (FEB21ER3SFBN-B10)
- B 4x2 515 Built Ready Wide Cab Alloy Tray MWB 5 Sp. Manual (FEB21ER4SFBC-B10)

WHEEL BASE

- 3400mm
- 3400mm

GVM (optional)

- 4,495kg
- 4,495kg

GCM (optional)

- 7,995kg
- 7,995kg

Performance

| | | |
|---|---|--------|
| Turning Circle (kerb to kerb - metres) | 11.0 | |
| Road Speed (km/h) at Max Engine Speed | 137 | |
| Engine Speed (rpm) at 100km/hr (top gear) | A 2346 | B 2420 |
| Gradeability at Rated GVM (theoretical)* | 45% | |
| Notes | *This is theoretical performance only. Actual performance may vary under different conditions | |

Mass (estimated)*

| | | |
|--------|---|----------|
| Front* | A 1525kg | B 1505kg |
| Rear* | 825kg | |
| Total* | A 2350kg | B 2330kg |
| Notes | * Mass (est.) includes oil and water but excludes spare wheel, tools & fuel. Weights provided are subject to 3.5% variation (+/-) | |


Dimensions (mm)

| | |
|-------------------------------|------|
| WFF (Width Front Fender) (mm) | 1995 |
| WRA (Width Rear Axle) (mm) | 1929 |
| WRT (Width Rear Track) (mm) | 1495 |
| Width Frame (mm) | 748 |

Body Builder's Notes

Built Ready

| | |
|--------------------------|--|
| Length (mm) | 4525 |
| Width (mm) | 2122 |
| Height (mm) | 330 |
| Overall Unit Length (mm) | 6255 |
| Features | <ul style="list-style-type: none"> • 260mm Two Piece Drop Sides (Center Split) • 4 Tonne Rated Slat Aluminum Floor* • Front Steps with Non-Slip Tread • 40mm Continues Rope Rail with • 65mm Tube Headboard with Mesh Infill And Grab Handles |
| Notes | * See MAXLOADING for vehicle capabilities |



Call 1800 033 557

or visit fuso.com.au

Unless specified in writing herein the accessories, applications, bodies or equipment depicted in this are for illustration purposes only and may not be available from Daimler Truck and Bus Australia Pacific Pty Ltd. (ABN 86 618 413 282) (DTB). No representation or warranty whatsoever is given in relation to any accessories, applications, bodies or equipment or suitability of same that are shown herein that may be manufactured, supplied or fitted by a party other than DTB. DTB reserves the right without notice or obligation to discontinue or make changes to the colour, designs, materials and specifications of the products and options referred to herein at any time. For the most current information and in order to ascertain which accessories, applications, bodies and equipment are available from DTB please contact your authorised FUSO Truck and Bus dealer. Fuso is a registered trademark of Daimler Truck and Bus Australia Pacific Pty Ltd. Copyright DTB. Reproduction in whole or part prohibited without written approval. Part Number TSX20A-SSV2. Valid from 01-Oct-19.